



WIRELESS

SKYFLO Master

The Skyflo™ Master is the heart of the Skyflo family of integrated wireless products, includes: Skyflo Pour Spout, Skyflo Fix, Skyflo Beer Monitor, Skyflo Optic Pearl & SKYTAG.

The Master remains on constant alert for RF signals sent from any of our numerous wireless products --- each product used in the Skyflo™ system is especially designed to meet the varied requirements of managing, controlling, and reporting sales and inventory information.

Using Skyflo software, the Master converts and stores data, (up to 24,000 messages), on both dispensing and open stock inventory information. Problems can be rapidly identified for prompt resolution. Detailed reports are easily printed when the Master is connected to a TMT88 printer, computer or a POS system.

<p>Skyflo™ Master Unit</p> <p>Size:</p> <p>LCD:</p> <p>Navigation button:</p> <p>Antenna:</p> <p>Frequency:</p> <p>Radio transmission:</p> <p>Electrical requirement:</p> <p>Power consumption:</p> <p>Memory:</p> <p>Serial port:</p> <p>Network:</p> <p>RTC:</p> <p>Printer:</p> <p>Pour times:</p> <p>Bartender ID:</p> <p>Interface capabilities:</p>	<p>Technical Specifications</p> <p>5.12" (130 mm) wide</p> <p>1.30" (33 mm) high</p> <p>3.94" (100 mm) deep</p> <p>1.50"</p> <p>Reset and Menu access</p> <p>2 pieces</p> <p>ISM 868 MHz free frequency in Europe</p> <p>ISM 915 MHz free frequency in USA & Australia</p> <p>150m in open air</p> <p>5 VDC @ 1A</p> <p>5 VA maximum</p> <p>512KB, external 256MB SD card</p> <p>RS232/RS485</p> <p>Ability to manage up to 2,000 RF devices with one Master</p> <p>Time record</p> <p>Esc/Pos, Db9</p> <p>Programmable for different time periods</p> <p>Identifies up to 128 bartenders</p> <p>- Sales Terminal (POS) with selectable protocols</p>
---	---

